

3! FLEX POB-MA

HYDROPHOBIC PRELOADED

877PA | 877PAY

Single piece, sterile, foldable aspheric hydrophobic acrylic intraocular lens (IOL) with UV blocker, optionally with blue light filter. The optic is monofocal. The IOL is available as part of a preloaded injector system.



CLEAR IOL



YELLOW IOL

POWER RANGE

Standard Powers

0.0 D → +9.0 D (1.0 D steps)
+10.0 D → +30.0 D (0.5 D steps)

Extreme Powers

-10.0 D → -1.0 D (1.0 D steps)
+31.0 D → +35.0 D (1.0 D steps)

MATERIAL

Hydrophobic acrylic with UV blocker and optional blue light filter

Refractive Index

1.47

Abbe Number

58

DESIGN

Optic Diameter
Overall Diameter

6 mm

13 mm

Optic Design

Aspheric - Aberration Neutral
Biconcave (-10.0 D → -1.0 D)
Biconvex (0.0 D → +35.0 D)

Nominal A-constant

118.9

Haptic Design

Posterior vaulting fenestrated C-loops with
0° angulation

PCO Prevention

360° sharp edge

Shelf Life

2.5 years after sterilization

INJECTION

Estimated Incision Size

2.2 mm

Compatible injector

POB-MA SINGLE-USE PRELOADED
INJECTOR

CONSTANTS

for optical and immersion ultrasound measurements

SRK/T A-Constant

A = 118.9

Haigis

a0 = 1.32
a1 = 0.4
a2 = 0.1

Hoffer Q

pACD = 5.46

Holladay I

SF = 1.7

Barrett Universal II

LF = 1.83

Holladay II

ACD = 5.49
SF = 1.73


The safety and performance of Medicontur IOLs have been tested in clinical investigations and the clinical data demonstrate that these IOLs meet the requirements of the state of the art.

MEDICONTUR

877PA | 877PAY


PRELOADED

3! FLEX | **POB-MA**
HYDROPHOBIC PRELOADED



MONOFOCAL

PRELOADED



MEDICNTUR

Medicontur
Medical Engineering Ltd
export@medicontur.com
www.medicontur.com

Head Office
Herczeghalmi út 1.
2072 Zsámbék
Hungary

International Office
Chemin du Champ-des-Filles 36
1228 Plan-les-Ouates
Switzerland / Geneva